DO NOT use this machine unless a instructor has instructed you in its safe use/operation and has given permission.



Safety glasses must be worn at all times in work areas.



Long and loose hair must be contained or constrained.



Appropriate footwear with substantial uppers must be worn.



Close fitting, protective clothing or a workshop apron is encouraged.



Rings and jewellery must not be worn.



Gloves must not be worn when operating this machinery.

PRE-OPERATIONAL SAFETY CHECKS

- 1. Check workspace and walkways to ensure no slip-hazards are present.
- 2. Locate and ensure you are familiar with the operation of the ON/OFF starter and E-Stop.
- 3. Ensure all guards are in place.
- 4. Check that the job is clamped tight in the chuck.
- 5. Remove all tools from the bed and slides of the machine.
- 6. Ensure correct speed for machining process is selected.
- 7. Remove the chuck key before starting the lathe.
- 8. Do not try to lift chucks or face plates that are too heavy for you.
- 9. Faulty equipment must not be used. Immediately report suspect machinery.

OPERATIONAL SAFETY CHECKS

- 1. Never leave the lathe running unattended.
- 2. Before making adjustments or measurements switch off and bring the machine to a complete standstill.
- 3. Do not attempt to slow/stop the chuck or revolving work by hand.
- 4. Avoid letting swarf build up on the tool or job. Stop the machine and remove it.
- 5. Always remove the chuck key from the chuck.
- 6. Do not store tools and parts on top of the machine.

HOUSEKEEPING

- 1. Switch off the machine and reset all guards to a fully closed position.
- 2. Leave the machine in a safe, clean and tidy state.

POTENTIAL HAZARDS

I O I LITTIAL HAZARDO		
Flying objects - chuck key Cut	tting tool injury Rotating machine parts	
Eye injuries Entanglement Sharp metal splinters or swarf		
Date of last review	Signature	

Signature __